

VERONA

white

PRIMI
CERAMICHE

SIZE

30x60 12"x24"


60x60 24"x24"

40x80 16"x32"

80x80 32"x32"

DIGITAL TECHNOLOGY





VARIAZIONE DI TONALITA'
SHADE VARIATION
VARIACION DE TONO

GLAZED PORCELAIN
PORCELANATO ESMALTADO
glossy

PEI 4

V1 tono uniforme – uniform appearance – monótona




VERONA 60X60










VERONA 30X60

Tech sheet



Packages

	Pcs. x 	m2. x 	kg x 	 x 	m2 x 	kg x 
80x80	3	1,92	48	28	53,76	1344
40x80	4	1,28	32	40	51,20	1280
60x60	4	1,44	31	40	57,60	1240
30x60	8	1,44	31	40	57,60	1240

Physical properties

Norms	Glazed Porcelain Tiles	values natural
UNI EN ISO 10545 - 3	Water Absorption	±1%
UNI EN ISO 10545 - 4	Bending strength	>-35N /mm ²
UNI EN ISO 10545 -12	Frost resistance index	Frost proof
UNI EN ISO 10545 - 9	Resistance to thermal shock	Resistant
UNI EN ISO 10545 - 2	Thickness	± 1%
UNI EN ISO 10545 - 2	Surface Flatness	± 0,2%
UNI EN ISO 10545 - 13	Chemical resistance	No Damage
UNI EN ISO 10545 - 14	Stain resistance	>4
ANSI A 137.1 : 2012	Dinamic coefficient of friction "DCOF"	0,43

